



ADDENDUM NO. 02

DISTRIBUTED BY: Eddie Nunez, CCS International, Inc.

DATE DISTRIBUTED: 6/10/2024

PROJECT: Town of Cicero Re-Bid RFP: Inclusive Playground

PAGES INCLUDING ATTACHMENTS: (4) pages.

NOTE: The following changes are hereby made to the Bid Documents and insofar as the original Bid Documents are inconsistent therewith, the changes herein shall govern. All bidders shall acknowledge this Addendum by inserting its number and date on their Bid Proposal.

CLARIFICATIONS TO BIDDER QUESTIONS:

The following are questions received per the RFP instructions along with corresponding responses.

1. Question: Will there be any info released about the FRP doors listed in the door schedule.
Response: For the FRP doors see specification section 081113 - Hollow Metal Doors and Frames.
2. Question: For the perforated panels, could you confirm if this is a premanufactured product or if this is something we should have custom made by a misc. metals contractor.
Response: For the perforated panel see detail 4/A5.0. The basis of design is from Artisan Panels, Inc. It was confirmed that they could supply the specified pattern, color and shape.

CHANGES AND CLARIFICATIONS TO RFP:

1. LP-1 panel specification.

DRAWINGS:

1. None.

ATTACHMENTS:

1. LP-1 Panel - Product Data Sheet


END OF ADDENDUM NO. 2

Product data sheet

Specifications

SQUARE D

Green Premium™



Load center, QO, 1 phase, 42 spaces, 52 circuits, 225A convertible main lugs, PoN, NEMA1, gnd bar, UL

QO142L225PG

Product availability: Stock - Normally stocked in distribution facility

Price*: 979.56 USD

Main

| | |
|----------------------|------------------|
| Marketing Trade Name | QO |
| Product Type | Load Center |
| Cover Type | Order separately |

Complementary

| | |
|--|--|
| Tightening Torque | Main lugs 250 lb.in, AWG 4...250 kcmil, aluminium/copper Cover 20 lb.in |
| Pon Convertible Mains (Lugs) | PoN Convertible Mains (lugs) |
| Rated Current | 225 A |
| Number Of Spaces | 42 |
| Max Short Circuit Current Rating | 65 kA |
| Maximum Number Of Single Pole Circuits | 52 |
| Maximum Number Of Tandem Breakers | 10 |
| Number Of Phases | 1 phase |
| Wire Size | AWG 6...300 kcmil aluminium/copper |
| Ground Bar | Grounding bar included (not installed) |
| Electrical Connection | Lugs |
| Wiring Configuration | 3-wire |
| Busbar Material | Tin plated copper: busbar |
| Enclosure Material | Welded sheet steel |
| Surface Finish | Baked enamel Gray |
| Box Number | 11 |
| Height | 37.99 in (965 mm) |
| Width | 14.25 in (362 mm) |

Environment

| | |
|---------------------------------------|---------------------------------|
| Enclosure Rating | NEMA 1 indoor |
| Ambient Air Temperature For Operation | 23 °F (-5 °C) 104 °F (40 °C) |
| Product Certifications | UL Listed |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US1DE3A10003 |
| Discount Schedule | DE3A |
| Gtin | 785901267430 |
| Returnability | Yes |
| Country Of Origin | US |

Packing Units

| | |
|------------------------------|----------------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 4.30 in (10.922 cm) |
| Package 1 Width | 14.80 in (37.592 cm) |
| Package 1 Length | 38.80 in (98.552 cm) |
| Package 1 Weight | 20.40 lb(US) (9.253 kg) |
| Unit Type Of Package 2 | PAL |
| Number Of Units In Package 2 | 27 |
| Package 2 Height | 43.50 in (110.49 cm) |
| Package 2 Width | 40.00 in (101.6 cm) |
| Package 2 Length | 48.00 in (121.92 cm) |
| Package 2 Weight | 588.00 lb(US) (266.712 kg) |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations

California Proposition 65

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov